



Deutsche
Qualität
Garantiert



SILICON HETEROJUNCTION PV MODULE

TME-132BDS 700W-720W

Enrich your energy yield

23.20%

MAXIMUM EFFICIENCY

132

HALF CELLS

30 YEARS

Performance Warranty

up to **30 YEARS***

Product Warranty

*The regular product warranty is 15 years, please refer to the latest version of AESOLAR Limited Warranty for the duration of the product warranty under special conditions. for extensions, please contact AESOLAR staff.



LID
RESISTANT



PID
RESISTANT



SALT CORROSION
RESISTANT



SAND
RESISTANT




AMMONIA
RESISTANT




LEAD TECHNOLOGY OF
METALLIZATION PROCESS



OUR PERFORMANCE WARRANTY



SYSTEM AND PRODUCT CERTIFICATIONS



IEC 61215 IEC 61730
Regular Production Surveillance
www.luv.com
ID 1111257249




AESOLAR

www.ae-solar.com

AE TME-132BDS 700W-720W

SILICON HETEROJUNCTION PV MODULE

BIFACIAL • DOUBLE-GLASS



Electrical specifications (STC*):

Parameter	Symbol	700	705	710	715	720
Nominal max. power	P_{max} (Wp)	700	705	710	715	720
Maximum operating voltage	V_{MPP} (V)	41.78	41.86	41.93	42.00	42.08
Maximum operating current	I_{MPP} (A)	16.77	16.86	16.95	17.05	17.13
Open-circuit voltage	V_{oc} (V)	49.83	49.92	50.01	50.09	50.18
Short-circuit current	I_{sc} (A)	17.82	17.91	18.00	18.10	18.19
Module efficiency	η (%)	22.50	22.70	22.90	23.00	23.20
Power tolerance	(W)	0~+5				
Maximum system voltage	(V)	1500				
Maximum series fuse rating	(A)	35				

*STC: Standard Test Conditions (irradiance 1000 W/m², cell temperature 25°C and air mass of AM1.5), measurement tolerance P_{max}: ±3%

Electrical specifications (NMOT*):

Parameter	Symbol	535	539	542	546	550
Nominal max. power	P_{max} (Wp)	535	539	542	546	550
Maximum operating voltage	V_{MPP} (V)	39.07	39.14	39.21	39.27	39.34
Maximum operating current	I_{MPP} (A)	13.68	13.76	13.83	13.91	13.98
Open-circuit voltage	V_{oc} (V)	46.69	46.78	46.86	46.93	47.02
Short-circuit current	I_{sc} (A)	14.61	14.68	14.67	14.84	14.92

*NMOT: Normal Module Operating Temperature (irradiance 800 W/m², ambient temperature 20°C, air mass of AM1.5 and wind speed of 1 m/s)

Bifacial electrical specifications

Max. power front-side	700		705		710		715		720	
P_{max} front (Wp)										
Backside Power Gain	5%	10%	5%	10%	5%	10%	5%	10%	5%	10%
Total equivalent power	735		770		740		776		792	
P_{max} equ (Wp)										
Module efficiency	23.63	24.75	23.84	24.97	24.05	25.19	24.26	25.41	24.47	25.63
η (%)										

*Bifacial Gain: The additional gain from the back side compared to the power of the front side at the standard test condition. It depends on the mounting (structure, height, tilt angle, etc.) and albedo of the ground.

Mechanical and design specification

Cell type	Silicon heterojunction technology, half-cut cells
No. of cells	132
Bifaciality	80 ± 5%
Front cover	2.0 mm glass, high transmission, AR coated, tempered
Encapsulation	POE
Back cover	2.0 mm white glazed glass, tempered
Junction box	IP68 rated, 3 bypass diodes
Frame	35 mm anodized aluminium alloy
Cable	1 x 4 mm, 350 mm length or customized
Connectors	MC 4 / MC 4 compatible
Dimension	2383 mm x 1302 mm x 35 mm
Weight	38.5 kg
Hail resistance	Max. Ø 25 mm at 23 m/s
Wind load	2400 Pa or 244 kg/m
Snow load	5400 Pa or 550 kg/m

Temperature ratings

Operating temperature	-40 to +85°C
Temp. coefficient of P_{max}	-0.24 %/°C
Temp. coefficient of V_{oc}	-0.22 %/°C
Temp. coefficient of I_{sc}	0.047 %/°C
Nom. operating cell temp. NOCT	43 ± 2°C

Packaging information

Packaging configuration	31 pcs / pallet
Loading capacity	558 pcs / 40 HQ
Size / Pallet	1350 mm x 1100 mm x 2520 mm (Upright)
Weight	1332 kg / pallet

The specifications and characteristics contained in this datasheet may deviate slightly from our actual products due to the product developments and uncertainty of measurement devices. The specifications included in the datasheet are subject to change without prior notice.